
Glo-Ball Basic 2


by Jasper Morrison , 1998



Table/desk lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide base. Gray painted, die-cast aluminum diffuser support. On the cable there is the electronic dimmer which allows the regulation of light brightness.







Mounting	Table
Environment	Indoor
Weight	5.3 Kg
Light sources available	1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220-240V
Power	MAX 250W
Battery	No
Supply included	Yes
Cord Length	1900 mm
Materials	Aluminum, Blown glass, Plastic
Colors	F3026000 - White
Certificate	

FLOS

Mini Glo-Ball Suspension

by Jasper Morrison , 2006

Suspension lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass. White painted, injection-molded PPS lamp-holder support.









Mounting	Pendant
Environment	Indoor
Weight	0.7 Kg
Light sources available	1 x LED 2W G9 240lm 2700K cod. RF26520 [e] No Dimmable 1 x LED 3W G9 290lm 2700K [e] cod. 28425 Non dimmable
Emergency	Without
Voltage	220-250V
Power	MAX 40W
Battery	No
Supply included	Yes
Cord Length	4000 mm
Materials	Blown glass
Colors	F4195009 - White
Certificate	

Glo-Ball Basic 1

by Jasper Morrison , 1998







Table/desk lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide base. Gray painted, die-cast aluminum diffuser support.On the cable there is the electronic dimmer which allows the regulation of light brightness.


Mounting	Table
Environment	Indoor
Weight	2.6 Kg
Light sources available	1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220-240V
Power	MAX 150W
Battery	No
Supply included	Yes
Cord Length	1900 mm
Materials	Aluminum, Blown glass, Plastic
Colors	F3021000 - White
Certificate	

Glo-Ball Basic Zero Dimmer

by Jasper Morrison , 2009



Table/desk lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide base. Gray painted, die-cast aluminum diffuser support.On the cable there is the electronic dimmer which allows the regulation of light brightness.





Mounting	Table
Environment	Indoor
Weight	1 Kg
Light sources available	1 x LED 8W E14 800lm 3000K cod. RF26565 [e] Dimmable 1 x LED 8W E14 700lm 2700K cod. RF26767 [e] Dimmable 1 x MAX 60W E14 HSGS 820lm 2800K [e] cod.RF19781 Dimmable 1 x LED 10W E14 900lm 2700K cod. RF26261 [e] Dimmable 1 x LED 10W E14 900lm 3000K [e] cod. RF26260 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220-240V
Power	MAX 60W
Battery	No
Supply included	Yes
Cord Length	1900 mm
Materials	Aluminum, Blown glass, Plastic
Colors	F3330009 - White
Certificate	

Mini Glo-Ball Table

by Jasper Morrison , 2003



Table/desk lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and an injection-molded, white PBT (polybutylenterephtalate) threaded ring nut. Injection-molded, white PBT (polybutylenterephtalate) cover, base/ lamp-holder support.

Mounting	Table
Environment	Indoor
Weight	0.4 Kg
Light sources available	1 x LED 2W G9 240lm 2700K cod. RF26520 [e]- NO DIMM. 1 x LED 3W G9 290lm 2700K [e] cod. 28425 Non dimmable
Emergency	Without
Switching	ON-OFF switch fitted on cord
Voltage	220-240V
Power	MAX 25W
Battery	No
Supply included	Yes
Cord Length	1500 mm
Materials	Glass
Colors	F4191009 - White
Certificate	









Glo-Ball Floor 3

by Jasper Morrison , 1998

Floor lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass and a die-cast threaded ring nut with alodine plating finish. Gray painted high-thickness steel base and stem and die-cast aluminum diffuser support. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Mounting	Floor
Environment	Indoor
Weight	18.9 Kg
Light sources available	1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220-250V
Power	MAX 250W
Battery	No
Supply included	Yes
Cord Length	1800 mm
Materials	Glass, Steel
Colors	F3030000 - Silver
Certificate	





Glo-Ball Floor 2

by Jasper Morrison , 1998


Floor lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass and a die-cast threaded ring nut with alodine plating finish. Gray painted high-thickness steel base and stem and die-cast aluminum diffuser support. On the cable there is the electronic dimmer which allows the regulation of light brightness.


Mounting	Floor
Environment	Indoor
Weight	12.5 Kg
Light sources available	1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220-250V
Power	MAX 250W
Battery	No
Supply included	Yes
Cord Length	1800 mm
Materials	Glass, Steel
Colors	F3032020 - Silver

Certificate

€ ∰ □







Glo-Ball Floor 1


by Jasper Morrison , 1998



externally acid-etched, hand blown, flashed opaline glass and a die-cast threaded ring nut with alodine plating finish. Gray painted high-thickness steel base and stem and die-cast aluminum diffuser support. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Floor lamp providing diffused light. Diffuser consisting of an








Mounting	Floor
Environment	Indoor
Weight	12 Kg
Light sources available	1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220-250V
Power	MAX 150W
Battery	No
Supply included	Yes
Cord Length	2300 mm
Materials	Glass, Steel
Colors	F3031020 - Silver
Certificate	




Glo-Ball Suspension 2 by Jasper Morrison , 1998

Suspension lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.








Mounting	Pendant
Environment	Indoor
Weight	5.6 Kg
Light sources available	1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable
Emergency	Without
Voltage	220-240V
Power	MAX 250W
Battery	No
Supply included	Yes
Cord Length	3700 mm
Materials	Blown glass, Steel
Colors	F3010061 - White
Certificate	




Glo-Ball Suspension 1 by Jasper Morrison , 1998

Suspension lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Gloss white painted pressed steel diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.







Mounting	Pendant
Environment	Indoor
Weight	2.7 Кд
Light sources available	1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 Dimmable 0 x LED 17W E27 2000lm 3000K [e] cod. RF26258 Dimmable
Emergency	Without
Voltage	220-250V
Power	MAX 150W
Battery	No
Supply included	Yes
Cord Length	3700 mm
Materials	Blown glass, Steel
Colors	F3005061 - White
Certificate	C € \$\$ \$ \$ 20